

Platin House Direct Package



Platin House Direct package

- Simple & quick to install.
- Submersible pump supplies harvested rainwater on demand to WCs, washing machine & external tap.
- Mains-on-Tap unit tops up the water level in the Platin tank when rainwater levels are low to guarantee continued water supply.
- The quiet & conveniently sized Mains-on-Tap unit will fit in a kitchen or utility cupboard for very low visual impact.
- Innovative float sensor detection on Mains-on-Tap unit ensures that the underground tank is kept supplied with mains water but only the amount necessary.

Scope of supply

- ① Underground tank (choice of tanks available, sizes vary according to property type)
- ② Telescopic lid (choice of telescopic lid available, depending on tank location)
- ③ Filter (Minimax filter supplied in accordance with type of tank)
- ④ Submersible pump with floating water intake
- ⑤ Mains-on-Tap unit
- ⑥ Float sensor (connected from Mains-on-Tap unit to the underground tank)

Supplied by others

- ⑦ 100mm diameter duct pipe to contain; float sensor cable, power cable for pump, also bringing mains water to underground tank as and when required
- ⑧ 100mm diameter drainage pipe connected from downpipes to the inlet at the top of the tank (all downpipes brought into one pipe for connection to the filter)
- ⑨ 100mm diameter pipe for overflow from the tank to mains drainage network or soakaway

Dimensions/weight	1,500 litres (400 US gallons)	3,000 litres (800 US gallons)	5,000 litres (1,350 US gallons)	7,500 litres (1,980 US gallons)
Length (l)	2,100mm (82.6")	2,450mm (96.5")	2,890 (113.8")	3,600 (141.7")
Width (w)	1,250mm (49.2")	2,100mm (82.7")	2,300mm (90.6")	2,250mm (88.6")
Height of tank shoulder (h)	700mm (27.5")	735mm (28.9")	950mm (37.4")	1250mm (49.2")
Height of dome collar (hd)	315mm (12.4")	315mm (12.4")	315mm (12.4")	315mm (12.4")
Ø tank dome (d)	800mm (31.5")	800mm (31.5")	800mm (31.5")	800mm (31.5")
Weight	80kg	170kg	240kg	360kg

