

Models and Specifications

Fire Protected Oil Tanks / Plastic



1350SLBFP



Capacity	Length	Width	Height	Weight
1,150 litres	2,680mm	870mm	1,665mm	195kg
			30min	60min
				238kg



2500HBFP

Capacity	Length	Width	Height	Weight
2,440 litres	2,840mm	1,520mm	1,630mm	290kg
			30min	60min
				337kg



1400VBFP

Capacity	Diameter	Height	Weight
1,200 litres	1,585mm	1,750mm	140kg
			30min
			171kg

Slimline tanks




For when space is restricted
and for easier movement

Fire Protected Oil Tanks / Steel

1000SBFP



Capacity	Length	Width	Height	Weight
1,000 litres	1,800mm	600mm	1,680mm	340kg
			30min	60min
				370kg



1650SBFP

Capacity	Length	Width	Height	Weight
1,670 litres	1,800mm	900mm	1,680mm	410kg
			30min	60min
				455kg



2300SBFP

Capacity	Length	Width	Height	Weight
2,325 litres	1,800mm	1,200mm	1,680mm	815kg
			30min	60min
				870kg



Specifications – Fire Protected Oil Tanks

	Plastic FP BO - 30min	Steel FP BO - 30min	Plastic FP TO - 30min	Steel FP TO - 30min	Plastic FP BO - 60min	Steel FP BO - 60min	Plastic FP TO - 60min	Steel FP TO - 60min
Feature	1350-2500L	1000-2300L	1350-2500L	1000-2300L	1350-2500L	1000-2300L	1350-2500L	1000-2300L
Fire Protection	✓	✓	✓	✓	✓	✓	✓	✓
2" BSP fill point	✓	✓	✓	✓	✓	✓	✓	✓
Overfill prevention valve	✓	✓	✓	✓	✓	✓	✓	✓
Vent	✓	✓	✓	✓	✓	✓	✓	✓
Manual float level gauge	✓	✓	✓	✓	✓	✓	✓	✓
Watchman Sonic	✓	✓	✓	✓	✓	✓	✓	✓
Lockable flip lid	✓	✓	✓	✓	✓	✓	✓	✓
1" bottom outlet	✓	✓	✓	✓	✓	✓	✓	✓
Top outlet	✓	✓	✓	✓	✓	✓	✓	✓
Fittings kit	✓	✓	✓	✓	✓	✓	✓	✓
Central lifting eye	✓	✓	✓	✓	✓	✓	✓	✓
Channel runners	✓	✓	✓	✓	✓	✓	✓	✓
Touch up paint	✓	✓	✓	✓	✓	✓	✓	✓
Codes	1350SLBFP-001-T 1400VBFP-001-T 2500HBFP-001-T	1000SBFP-001-T 1650SBFP-001-T 1650SBFP-001-T	1350SLBFP-002-T 1400VBFP-002-T 2500HBFP-002-T	1000SBFP-002-T 1650SBFP-002-T 1650SBFP-002-T	1350SLBFP-003-T 1400VBFP-003-T 2500HBFP-003-T	1000SBFP-003-T 1650SBFP-003-T 1650SBFP-003-T	1350SLBFP-004-T 1400VBFP-004-T 2500HBFP-004-T	1000SBFP-004-T 1650SBFP-004-T 1650SBFP-004-T

What is FirePro®?



FirePro® is a tier-one bunded oil tank that's integrally fitted with a unique, patented fire jacket providing 30 or 60-minute fire protection.

Our unique product provides compliant installation as close as 300mm from the walls or boundaries and can even be installed inside domestic outbuildings.

FirePro® is a perfect choice when:

- Replacing an oil tank in a location which is no longer compliant.
- Space is limited, and you're struggling to comply with Building Regulations.
- You want to locate your oil tank discreetly to preserve the look and feel of your outside areas.
- You want to avoid lengthy installations, building works and unsightly fireboards.
- You want to install a tank safely inside a domestic outbuilding (e.g. garage) or under a lean-to.



Who can install and certify a fire rated oil tank?

a. Competent Persons

- i. Technicians within Competent Persons Schemes such as the Association of Plumbing and Heating Contractors (APHC) can fit and certify the oil tank without prior approval from building control.

b. End User/Installer

- i. Tuffa have partnered with Approved Inspectors Stroma and developed a simple 4-step process that Stroma can self-certify, often remotely.

- **Step 1:** Complete the Stroma application form and send to them directly. This must be submitted a minimum of 7 days before works commence on site.
- **Step 2:** Provide any images or additional information as required.
- **Step 3:** Once the tank is installed, email the final installation photos and Compliance Declaration Form to Stroma.
- **Step 4:** Pay the £150.00 plus VAT sign-off fee and wait for the certification direct from Stroma.

