

NEW

TrolleyMaster®

Handy and universal mobile tank for Diesel and AdBlue® distribution in any terrain

Available capacities: 60 and 100 L



TrolleyMaster® - AdBlue®

Versatile use:



TrolleyMaster® - Diesel



For more information about TrolleyMaster®:
Tel.: **+48 61 814 44 00**, Email: **tankinfo@kingspan.com**
or visit us at: **www.kingspanenergymanagement.com**

TrolleyMaster®

Discover the benefits of handy
TrolleyMaster® mobile tanks:



Off-road rubber wheels

Two solid rubber wheels with a diameter of 250 mm allow for transporting the tank in every place, unpaved or uneven.



Dedicated nozzle pocket

Pocket collects liquid drops from the nozzle and protects the nozzle during tank transport. It can be easily unscrewed and cleaned.



Groove for delivery hose

The profiled groove makes it possible to wrap the hose around the tank while on the move.



Comfort of refueling

An efficient pump with battery clamps allows you to quickly refill diesel/AdBlue®.



Ergonomic handle

Comfortable, profiled handle provides a secure grip when pulling and lifting the tank.



Lockable ball valve

Lockable valve protects against liquid leakage from the product during transport.



Mobility

Safe diesel/AdBlue® transport directly to the workplace of machines, including boats and equipment operating in difficult terrain



Trustworthy Quality

Durable construction, corrosion free and weatherproof



Saving Time and Resources

Mobile tanks are compact and perfect in the agricultural, construction or forestry industry, because they let you avoid equipment downtime during work



Peace of Mind

2 years guarantee on the tank and equipment

Equipment:

- | | |
|---|--|
| 1. TrolleyMaster® tank | 8. 12 V DC or 24 V DC pump to choose |
| 2. Groove for wrapping the delivery hose during transport | 9. Flexible delivery hose 3 m |
| 3. Nozzle pocket | 10. 3/4" ball valve |
| 4. Automatic nozzle with a rotary joint | 11. Non-slip handles |
| 5. Transport handle | 12. Profiled corners for fastening straps |
| 6. Battery clamps | 13. Solid rubber wheels with a Ø 250 mm diameter |
| 7. Fuel cap with breathing valve | 14. K24 digital flowmeter (optional) |

Dimensions:

		TrolleyMaster® 60	TrolleyMaster® 100
Capacity		60 Litres	100 Litres
Dimensions	Length	380 mm	380 mm
	Width	380 mm	440 mm
	Height	913 mm	1093 mm



For more information about TrolleyMaster®:
Tel.: +48 61 814 44 00, Email: tankinfo@kingspan.com
or visit us at: www.kingspanenergymanagement.com