

# LUS.2250



## 2250 LITRE STEEL BUNDED LUBE OIL TANK



### TANK:

The inner tank provides the required storage area, the outer tank forms the required bund with capacity for 110% of the total liquid being stored. The tank is suitable for storage of lube oil, diesel, kerosene and certain other oils. Please check before usage.

### THIS TANK COMPLIES WITH:

Prevention Guidelines (England & Wales) 2002  
PPG2.  
BS799 pt5

### SPECIFICATIONS:

- Tough steel construction
- 2250 litres (495 galls) capacity
- 3 No. 2" top sockets (for fill, pump & spare)
- 1 No. 1 1/2 " top socket (for gauge)
- 1 No. 1 1/2" bund socket (for bund gauge)
- 1 No 2" vent with cowl fitted pump
- 1 No. 1" suction drain socket (plugged)
- 1 No. 10mm return socket
- 1 No. 100mm x 25mm vent/overflow cut out
- Mounted on 100mm x 50mm high channel support bearers
- 10 year warranty

### EQUIPMENT OPTIONS:

- 230v Oil Pump Kit c/w 15m Hose Reel, Nozzle/Meter & Drip Tray
- Air Operated Oil Pump Kit 3:1 Ratio c/w 15m Hose Reel, Nozzle/Meter & Drip Tray
- Air Operated Oil Pump Kit 5:1 Ratio c/w 15m Hose Reel, Nozzle/Meter & Drip Tray

### DIMENSIONS:

Length: 1830mm  
Width: 1220mm  
Height: 1220mm  
Weight: 370kg

