DIS.P2000



1900 LITRE PORTABLE BUNDED DIESEL PORTATANK



TANK:

This 1900 litre robust Diese! PORTATANK is made from 3mm steel. It is suitable for the transportation of Diesel and certain other oils (please check before usage). Ideal for use with plant, generators or for refuelling machinery. Complete with ADR & UN approval, fulfilling the requirements of the European Agreement concerning the International Carriage of Dangerous Goods by Road, dated 01 January 2005 (ADR 2005).

SPECIFICATIONS:

- 5 year tank warranty, 1 year pump warranty
- Capacity: 1900 Litres
- 110% bunded (steel in steel) to ensure compliance with (PPG2)
- Gas sprung lockable lid
- Tank colour: Grey (colour of choice available)
- Lid colour: Orange (colour of choice available)
- Lacquering: C3 A 3.11
- Inner baffles for liquid stabilisation whilst in transit
- Removable top, for access to inner tank and cleaning
- Inner tank has manway access for cleaning
- 4 way forklift pockets
- Easily securable with strapping hooks
- Welded lifting eyes for lifting when full
- ADR, UN & CE approved (certificates provided with tank)
- Mesh grid on floor area, to prevent fuel residue on hose
- Earth point on tank

- 3" Fill Point Vent
- Overfill sensor Contents gauge
- Lever ball valve for refuelling
- 1 x 1" suction port for pump with vane, suction tube, non-return valve & strainer
- 3 x $\sqrt[3]{4}$ " suction ports for plant/generator with suction tube, non-return valve & strainer
- 3 x 1/2" return ports for plant/generator

DIMENSIONS:

Length: 2580mm Width: 1180mm Height: 1260mm

Weight (empty): approx. 835 kg (empty) approx. 2415 kg (full)

EQUIPMENT OPTIONS:

- Manual / semi rotary pump
- 50 LPM 12v pump kit
- 50 LPM 24v pump kit
- 55 LPM 110v pump kit
- 55 LPM 230v pump kit
- Digital flow meter
- Generator flow & return hose set



PORTATANK EQUIPMENT OPTIONS:

PUMP OPTIONS:



EQUIPMENT OPTIONS: Optional Optional



Digital Flow Meter



Generator Flow & Return Hose Set



PORTATANK DETAILS:

















66

The robust Diesel *PORTATANK* is suitable for the transportation of Diesel, making it ideal for use with plant, generators or for refuelling machinery.























